



# ARCHERY

BUILT THE **BEST**. BY THE **BEST**. FOR THE **BEST**.

## ALPHA

OUR LATEST DOUBLE-CALIPER STYLE RELEASE.

THE ALPHA FEATURES A ROLLER-SEAR DESIGN AND AN ADJUSTABLE TRIGGER. THE BLACKENED STAINLESS STEEL JAWS ARE FULLY RADIUSSED, AND THE ALPHA CAN BE USED OFF THE BOWSTRING OR WITH A STRING LOOP. IT'S SETTING NEW STANDARDS IN THE DUAL-CALIPER RELEASE WORLD.

### Available connectors:

SWIVEL STEM<sup>®</sup> — 11 LENGTH SETTINGS

FLEX CONNECTOR SYSTEM<sup>®</sup> — INFINITE LENGTH ADJUSTMENT

COMPLETE INSTRUCTIONS INCLUDED INSIDE PACKAGE. \*PATENTS PENDING.

101 TUG BRANCH ROAD / CLAY CITY, KY / 40312

**B3ARCHERY.COM / 606.612.5215**



# ARCHERY

BUILT THE **BEST**. BY THE **BEST**. FOR THE **BEST**.

- FLEX CONNECTOR<sup>®</sup>
- SWIVEL STEM<sup>®</sup>

## ALPHA

BLACK STAINLESS  
STEEL JAWS

ADJUSTABLE  
ROLLER SEAR



RELEASES • BROADHEADS • SIGHTS

## Adjustment Instructions

### Trigger Travel Adjustment

1. LOCATE THE 4-40 TENSION/TRAVEL ADJUSTMENT SCREW AT THE TRIGGER'S BASE.
2. INCREASE TRAVEL BY TURNING THE SET SCREW CLOCKWISE. DECREASE TRAVEL BY TURNING THE SET SCREW COUNTER-CLOCKWISE.
3. TEST AFTER EACH 1/16TH TURN OF THE SET SCREW. IT IS POSSIBLE TO SET YOUR TRIGGER TENSION TOO SENSITIVE IF TURNING THE SET SCREW TOO FAR (COUNTER-CLOCKWISE).

### Length Adjustments - Patents Pending

#### SWIVEL STEM CONNECTOR

1. REMOVE THE 6/32 CAP SCREW FROM THE SIDE OF THE RELEASE HEAD.
2. SLIDE THE HEAD OF THE RELEASE TO THE DESIRED LENGTH, AND RE-INSERT THE SCREW INTO THE CORRESPONDING HOLE ON THE HEAD AND TIGHTEN.

**DO NOT OVERTIGHTEN THE SCREW. \*\*\***

**BE SURE TO INSERT THE SCREW INTO THE SIDE OF THE RELEASE HEAD WITH THE LARGER DIAMETER HOLES. \*\*\***

#### FLEX CONNECTOR

1. LOOSEN THE 1/4-28 CONE POINT SET SCREW, WHICH IS LOCATED ON THE CENTER OF THE METAL STRAP BRACKET SEWN INTO THE RELEASE STRAP.
2. SLIDE THE FLEX CONNECTOR TO THE DESIRED LENGTH AND TIGHTEN THE SET SCREW. MAKE SURE TO KEEP THE SAFETY KNOT IN THE EXCESS NYLON.

**DO NOT OVERTIGHTEN THE SET SCREW. \*\*\***

## Maintenance and Use

1. THIS RELEASE MAY BE USED WITH A STRING LOOP OR DIRECTLY OFF OF YOUR BOWSTRING.
2. DO NOT ALLOW RELEASE JAWS TO CONTACT METAL NOCK SETS OR METAL D-LOOPS.
3. IF YOUR RELEASE BECOMES WET, ALLOW TO AIR DRY AND LUBRICATE ROLLER SEAR.



**101 TUG BRANCH ROAD / CLAY CITY, KY / 40312**  
**B3ARCHERY.COM / 606.612.5215**



**BUILT THE BEST. BY THE BEST. FOR THE BEST.**