



ARCHERY

BUILT THE **BEST**. BY THE **BEST**. FOR THE **BEST**.

the **CLAW**

OUR LATEST BLACKENED STAINLESS HOOK DESIGN.

THE CLAW FEATURES OUR ROLLER-SEAR HOOK RELEASE AND IS SPECIFICALLY BUILT FOR STRING-LOOP SHOOTERS. OTHER FEATURES INCLUDE ANGLED FORWARD TRIGGER, FLEX OR SWIVEL STEM CONNECTOR, AND TRAVEL/SENSITIVITY ADJUSTMENT. THE CLAW'S OPEN-HOOK DESIGN ALLOWS FOR FAST AND SIMPLE LOADING IN THE FIELD AT THE MOMENT OF TRUTH. WHETHER YOU ARE TROPHY HUNTING OR TRYING TO GET ON THE PODIUM, THE CLAW IS THE RELEASE FOR YOU.

Available connectors:

SWIVEL STEM — 11 LENGTH SETTINGS

FLEX CONNECTOR SYSTEM — INFINITE LENGTH ADJUSTMENT

COMPLETE INSTRUCTIONS INCLUDED INSIDE PACKAGE.

101 TUG BRANCH ROAD / CLAY CITY, KY / 40312

B3ARCHERY.COM / 606.612.5215



ARCHERY

BUILT THE **BEST**. BY THE **BEST**. FOR THE **BEST**.

- FLEX CONNECTOR
- SWIVEL STEM

the **CLAW**

- STAINLESS STEEL HOOK
- ADJUSTABLE ROLLER SEAR



RELEASES • BROADHEADS • SIGHTS

Adjustment Instructions

Trigger Travel Adjustment

1. LOCATE THE 4-40 TENSION/TRAVEL ADJUSTMENT SCREW AT THE TRIGGER'S BASE.
2. INCREASE TRAVEL BY TURNING THE SET SCREW CLOCKWISE. DECREASE TRAVEL BY TURNING THE SET SCREW COUNTER-CLOCKWISE.
3. TEST AFTER EACH 1/16TH TURN OF THE SET SCREW. IT IS POSSIBLE TO SET YOUR TRIGGER TENSION TOO SENSITIVE IF TURNING THE SET SCREW TOO FAR (COUNTER-CLOCKWISE).

Length Adjustments - Patents Pending

SWIVEL STEM CONNECTOR

1. REMOVE THE 6/32 CAP SCREW FROM THE SIDE OF THE RELEASE HEAD.
2. SLIDE THE HEAD OF THE RELEASE TO THE DESIRED LENGTH, AND RE-INSERT THE SCREW INTO THE CORRESPONDING HOLE ON THE HEAD AND TIGHTEN.

DO NOT OVERTIGHTEN THE SCREW. ***

BE SURE TO INSERT THE SCREW INTO THE SIDE OF THE RELEASE HEAD WITH THE LARGER DIAMETER HOLES. ***

FLEX CONNECTOR

1. LOOSEN THE 1/4-28 CONE POINT SET SCREW, WHICH IS LOCATED ON THE CENTER OF THE METAL STRAP BRACKET SEWN INTO THE RELEASE STRAP.
2. SLIDE THE FLEX CONNECTOR TO THE DESIRED LENGTH AND TIGHTEN THE SET SCREW. MAKE SURE TO KEEP THE SAFETY KNOT IN THE EXCESS NYLON.

DO NOT OVERTIGHTEN THE SET SCREW. ***

Maintenance and Use

1. THIS RELEASE MAY BE USED WITH A STRING LOOP ONLY.
2. DO NOT USE THIS RELEASE WITH A METAL D-LOOP.
3. IF YOUR RELEASE BECOMES WET, ALLOW TO AIR DRY AND LUBRICATE ROLLER SEAR.



101 TUG BRANCH ROAD / CLAY CITY, KY / 40312

B3ARCHERY.COM / 606.612.5215



BUILT THE BEST. BY THE BEST. FOR THE BEST.