A R C H E R Y BUILT THE BEST. BY THE BEST. FOR THE BEST.



INNOVATIVE THUMB-BUTTON DESIGN.

THE EXIT PRO RELEASE FEATURES OUR PATENT PENDING LOCK-AND-LOAD DESIGN, WITH A FULLY RADIUSED HANDLE AND POLISHED HARDENED STAINLESS STEEL SEARS. PRO HANDLE FEATURES OUR PATENTED STAR DRIVE SYSTEM, WHICH ALLOWS FOR DIFFERENT ARMS WITH MULTIPLE POSITIONS AVAILABLE. IF YOU WANT A RELEASE WITH ENDLESS ADJUSTABILITY CHECK OUT THE EXIT PRO.

> COMPLETE INSTRUCTIONS INCLUDED INSIDE PAGKAGE. PATENTED DESIGN AND A PATENT PENDING.

> > 101 TUG BRANCH ROAD CLAY CITY, KY / 40312

> > > B3ARCHERY.COM 606.612.5215



A R C H E R Y BUILT THE BEST. BY THE BEST. FOR THE BEST.

LOCK AND LOAD DESIGN

FULLY ADJUSTABLE Handle STAINLESS STEEL SEARS

> TRAVEL AND TENSION ADJUSTMENT



Adjustment Instructions

Travel Adjustment

- 1. THE CAP SCREW LOCATED IN THE TRIGGER AT THE BASE OF THE HANDLE IS YOUR TRAVEL ADJUSTMENT SCREW.
- 2. TO INCREASE TRAVEL, ROTATE THE CAP SCREW COUNTER-CLOCKWISE. TO DECREASE TRAVEL, ROTATE THE SCREW CLOCKWISE.
- 3. TO DRY RELEASE, BLOW OUT WITH COMPRESSED AIR.

PLEASE TEST AFTER ANY ADJUSTMENT.

DO NOT OVERTIGHTEN.

Tension Adjustment

- 1. LOCATE THE SET SCREW ON THE SIDE OF YOUR RELEASE HANDLE. TURN THIS SET SCREW CLOCKWISE TO INCREASE TENSION AND COUNTER-CLOCKWISE TO DECREASE TENSION.
- 2. NEVER TURN MORE THAN 2 FULL TURNS (IN EITHER DIRECTION) FROM THE FACTORY SETTING.
- ***ALL ADJUSTMENTS SHOULD BE MADE IN 1/16TH TURN INCREMENTS.

PLEASE TEST AFTER ANY ADJUSTMENT.

DO NOT OVERTIGHTEN.

To Change Finger Locations and/or Arms

- 1. REMOVE THE 6-32 X 3/8 SCREW.
- 2. MOVE FINGER PIECE TO DESIRED LOCATION AND RE-TIGHTEN THE 6-32 X 3/8 SCREW.
 - PLEASE TEST AFTER ANY ADJUSTMENT.

DO NOT OVERTIGHTEN.



101 TUG BRANCH ROAD / CLAY CITY, KY / 40312 B3Archery.com / 606.612.5215

