



# ARCHERY

BUILT THE **BEST**. BY THE **BEST**. FOR THE **BEST**.



DOUBLE-CALIPER RELEASE.

THE RIVAL FEATURES BLACK ALUMINUM JAWS AND A CURVED TRIGGER. AVAILABLE IN BOTH OF OUR PATENTED CONNECTOR SYSTEMS, THE FLEX OR SWIVEL. THE RIVAL IS A GREAT LOOKING, TOP-QUALITY RELEASE THAT WILL PERFORM WELL WITHOUT BREAKING THE BANK.

COMPLETE INSTRUCTIONS INCLUDED INSIDE PACKAGE.  
PATENTED DESIGN.

101 TUG BRANCH ROAD / CLAY CITY, KY / 40312  
**B3ARCHERY.COM / 606.612.5215**



# ARCHERY

BUILT THE **BEST**. BY THE **BEST**. FOR THE **BEST**.

- FLEX CONNECTOR
- SWIVEL STEM



DUAL JAWS  
BLACK  
ROLLER SEAR



RELEASES • BROADHEADS • SIGHTS

## Adjustment Instructions

### Length Adjustments -

#### SWIVEL STEM CONNECTOR

1. REMOVE THE 6/32 CAP SCREW FROM THE SIDE OF THE RELEASE HEAD.
2. SLIDE THE HEAD OF THE RELEASE TO THE DESIRED LENGTH, AND RE-INSERT THE SCREW INTO THE CORRESPONDING HOLE ON THE HEAD AND TIGHTEN.  
**PLEASE TEST AFTER ANY ADJUSTMENT.**  
**DO NOT OVERTIGHTEN THE SET SCREW.**

BE SURE TO INSERT THE SCREW INTO THE SIDE OF THE RELEASE HEAD WITH THE LARGER DIAMETER HOLES. \*\*\*

#### FLEX CONNECTOR

1. LOOSEN THE 1/4-28 CONE POINT SET SCREW, WHICH IS LOCATED ON THE CENTER OF THE METAL STRAP BRACKET SEWN INTO THE RELEASE STRAP.
2. SLIDE THE FLEX CONNECTOR TO THE DESIRED LENGTH AND TIGHTEN THE SET SCREW. MAKE SURE TO KEEP THE SAFETY KNOT IN THE EXCESS NYLON.

**PLEASE TEST AFTER ANY ADJUSTMENT.**

**DO NOT OVERTIGHTEN THE SET SCREW.**

### Maintenance and Use

1. THIS RELEASE MAY BE USED WITH A STRING LOOP OR DIRECTLY OFF OF YOUR BOWSTRING.
2. DO NOT ALLOW RELEASE JAWS TO CONTACT METAL NOCK SETS OR METAL D-LOOPS.
3. ALLOW TO AIR DRY AND LUBRICATE ROLLER SEAR AS NEEDED.



**101 TUG BRANCH ROAD / CLAY CITY, KY / 40312**  
**B3ARCHERY.COM / 606.612.5215**

